


BRECON
Cologne
Germany



BRECON
smart vibration technology



General catalog

Program 2017

External vibrators
Internal vibrators
Control systems
Accessories

Internal vibrator

3

BRECON Internal vibrator INTEQ
110 V or 230 V
with integrated frequency converter



Type	Head diameter [mm]	Head length [mm]	Nominal current [A]	Voltage [V]		Power [kVa]	Weight [kg]
18 031 029	31	320	3,50	230	12.000 1/min	0,80	12,6
18 038 029	38	370	3,70	230		0,85	13,9
18 050 029	50	390	6,10	230		1,40	17,9
18 058 029	58	360	7,00	230		1,70	18,6
18 065 029	65	350	7,60	230		1,80	19,8
18 031 030	31	320	3,50	110	12.000 1/min	0,80	12,6
18 038 030	38	370	3,70	110		0,85	13,9
18 050 030	50	390	6,10	110		1,40	17,9
18 058 030	58	360	7,00	110		1,70	18,6
18 065 030	65	350	7,60	110		1,80	19,8

* With 5 m hose, 10 m power cable and schuko plug

BRECON Internal vibrator - pneumatic
with 2 m hose



Type	Head diameter [mm]	Head length [mm]	Free air [l/min]	Air pressure [bar]	Weight [kg]
18 028 401	28	204	500	6 - 7 bar	4,4
18 035 401*	35	220	608		6,0
18 045 401*	45	252	736		8,0
18 055 401*	55	259	820		9,0
18 065 401*	65	277	1.018		10,0
18 075 401*	75	299	1.218		15,0
18 085 401	85	323	1.600		19,0
18 105 401	105	274	2.100		23,0
18 140 401	140	508	2.880		35,0
18 160 401	160	508	3.750		41,5

* Also available with vulkollan cap on request at extra costs (please indicate when ordering)



BRECON

Vibrationstechnik GmbH

P.O. Box 45 01 69
D-50876 Cologne

Phone: +49 (0)2 21 95 44 27-0
Fax: +49 (0)2 21 95 44 27-7

info@brecon-vibration.com
www.brecon-vibration.com